

FLOS

■ F0406030 Black


Arrangements Round Small

Designed by Michael Anastassiades, 2018



21W - 1068lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

| | |
|-------------------|---------------------|
| EAN | 8059607014103 |
| Mounting | Suspension |
| Environments | Indoor dry location |
| Light Source Type | LED |
| LED type | LED Module |
| Power (W) | 21 |
| System flux (lm) | 1068 |

Physical

| | |
|---------------------|-------|
| Colour | Black |
| Length (mm) | 398 |
| Cord length (mm) | 2500 |
| Net weight (kg) | 0.41 |
| Package height (mm) | 45 |
| Package width (mm) | 480 |
| Package length (mm) | 510 |
| Package volume (m3) | 0.01 |
| IP internal | 20 |

Download

| | |
|-----------------------|-------|
| Mounting instructions | ↓ PDF |
| Spare Parts | ↓ PDF |

Photometric Files

| | |
|-----------|-------|
| LDT / IES | ↓ LDT |
|-----------|-------|


Technical Drawings

| | |
|-------|-------|
| 2D | ↓ ZIP |
| 3D | ↓ ZIP |
| 🔒 Bim | ↓ ZIP |



| |
|----|
| IP |
| 20 |

Schematic light drawing



Luminous flux luminaire
1068 lm

Photometric


| | |
|--------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | 2700 |

Electrical

| | |
|----------------------|---------------------------------------|
| Insulation class | III |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 48 |
| LED voltage Vf (Vdc) | null |
| Driver | Remote |
| Dimmable | Yes |
| Dimming type | Electronic 48V |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |
| Batteries inside | No |


Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional


Accessories & Power Supply



REQUIRED

F0415030

Arrangements Big Rose



REQUIRED

F0416030

Arrangements Small Rose



REQUIRED

F0418030

Arrangements Recessed Rose